

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	revisions								
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED				
1		RELEASED FOR PRODUCTION.	6/17/2016	DPD	JAG				
2		-1, -3, & -5 CH'D MATERIAL WAS 4140/4142 Q&T IS 4140/4142, ADDED HEAT TREAT RC 28-32, -1 CH'D DIM WAS .50 IS 2X .50, CH'D ZINC PLATE FINISH SPEC WAS ASTM B633 TYPE II SC 2 IS ASTM B633 TYPE I SC 2.	11/8/2016	RJC	JAG				





NOTES: 1. REF. AIRBUS T/N: M633V3000124. 2. PART OF KIT RBEM633V3000102.



MGB BAR PIN EXCHANGE


DWG NO. RBEM633V3000124 UNLESS OTHERWISE SPECIFIED

G	HEAT TREAT FINISH SPEC			DIMENSIONS ARE IN INCHES				
2	DRAWN BY:	DUERFE				IAL LIMITS APPLY		
	CHECKED:	CLOUGH	1		AFTER PLA			
3	OPPS APPR:	APPR: ANDERSON			3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009			
4	QA APPR:	LINDSAY			USED ON MODEL			
1	APPROVED:	OVED: GILBERT			H175			
1	SCALE	1.2	DATE	3/2	8/2016	SHEET 1 OF 4		

									HEAT
ASSY QTY	ASSY QTY	В/О	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	TREA FINIS SPEC
			-1	1	TUBE	4140/4142		2	DRAV
			-3	1	NUT	4140/4142		_	OPPS
			-5	1	THREADED ROD	4140/4142		4	QA A
		B/O	-7	1	WASHER	STEEL	M6, CLASS 10.9 (MCMASTER-CARR #91455A120)	1	APPR
		B/O	-9	1	HEX NUT	STEEL	M6 X 1mm, CLASS 10 (MCMASTER-CARR #92497A350)	1	SCA

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS									
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED					
2	16-0128	-1 CH'D DIM WAS .50 IS 2X .50, CH'D MATERIAL WAS 4140/4142 Q&T IS 4140/4142, ADDED HEAT TREAT RC 28-32, CH'D ZINC PLATE FINISH SPEC WAS ASTM B633 TYPE I SC 2 IS ASTM B633 TYPE I SC 2.	11/8/2016	RJC	JAG					



NOTES: 1. DUAL FINISH:

1ST: ZINC PLATE, ASTM B633 TYPE I SC2. 2ND: POWDER COAT YELLOW, FED #13538.

 $2\$ no powder coat this surface.





	RBE	M63	33	/30001:	24-1)		
MAT'L 4140/4142 HEAT RC 28-32 TREAT				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8				
FINISH SEE NOTE 1				.XX ± .01 ANGLES ±.5° .X ± .1 SURFACES = 125				
SPEC				1. BREAK ALL SHARP EDGES				
DRAWN BY: DUERFELDT			.015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY					
CHECKED:	CLOUGH	1		AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009				
OPPS APPR:	ANDERS	SON						
QA APPR: LINDSAY		USED ON MODEL						
APPROVED: GILBERT				H175				
SCALE	1.1	DATE	3/2	28/2016	SHEET 2 OF 4			


TUBE

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS .								
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED				
2	16-0128	-3 CH'D MATERIAL WAS 4140/4142 Q&T IS 4140/4142, ADDED HEAT TREAT RC 28-32	11/8/2016	RJC	JAG				









TITLE

MGB BAR PIN EXCHANGE

DWG NO.


RBEM633V3000124-3

2


						_
MAT'L 4140/4				S OTHERWISE SPECIF NSIONS ARE IN INCHE		
REAT RC 28	-32			.XXX ± .005		.5
	ER COAT Y	ELLOW	.XX ± .01	25/		
SPEC FED#	13538			1. BREAK ALL SHARP EDGES		
DUERFE		ELDT		.015 x 45° C		
CHECKED:	CLOUGH			DIMENSIONAL LIMITS APPLY AFTER PLATING INTERPRET DIM AND TOL PER ASME Y14.5M-2009		
OPPS APPR:	ANDERSON					
QA APPR:	LINDSAY			USED ON MODEL		
APPROVED:	GILBERT		H175			
SCALE	1:1	:1 DATE 3/2		28/2016 SHEET 3 OF 4		


(-3)

NUT



	REVISIONS REVISIONS									
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED					
2	16-0128	-5 CH'D MATERIAL WAS 4140/4142 Q&T IS 4140/4142, ADDED HEAT TREAT RC 28-32	11/8/2016	RJC	JAG					







DART

TITLE

MGB BAR PIN EXCHANGE

DWG NO.

RBEM633V3000124-5

REV 2

MAT'L 4140/4	142		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES				
HEAT RC 28-	-32		.XXX ± .005 FRACTIONS ± 1/8				
FINISH ZINC F	PLATE		.XX ± .01 .X ± .1	ANGLES ±.5° SURFACES = 125/			
SPEC ASTM	B633 TYPE I	SC 2		1. BREAK ALL SHARP EDGES			
DRAWN BY:	DUERFELDT			.015 x 45° OR .015R - 2. DIMENSIONAL LIMITS APPLY AFTER PLATING - 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009			
CHECKED:	CLOUGH						
OPPS APPR:	ANDERSON						
QA APPR:	LINDSAY			USED ON MODEL			
APPROVED:	GILBERT			H175			
SCALE	1:1	DATE	3/2	28/2016	SHEET 4 OF 4		

(-5)

THREADED ROD